



FEATURES

Intended Use:	Interior
Installation:	Binary
Body/Structure:	Aluminum
Painting:	Interior polyester powder coating
Finish:	Black
Reflector/Optics:	PMMA LED Lens

TECHNICAL DATA

Beam:	Concentrating-Diffusing 10-55°
Insulation class:	3
Weight:	0.420 kg
IP grade:	20
Lamp included:	Yes
Overall power:	20 W
Appliance flow:	2005 lm
Nominal duration:	50.000 (h) L90 B20
Color temperature:	3000 K
Color rendering index:	>90
Color consistency:	3 SDCM




NOTES


Size: ø 65 x 135mm



TECHNICAL DRAWING



PHOTOMETRIC CURVES



COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.