



L	680 mm
A	680 mm
H	187 mm

ILLUMINOTECHNICAL CHARACTERISTICS

Luminous efficiency 100%.
 Initial luminous flux of the luminaire 14957 lm.
 Symmetric wide direct distribution.
 Installation Interdistance Transv.D = 0.91 x hu - Long.D = 1.24 x hu.
 UGR <22 (EN 12464-1).
 Luminous efficacy 136 lm/W.
 Lifetime (L90/B10): 30000 h. (tq+25°C)
 Lifetime (L85/B10): 50000 h. (tq+25°C)
 Lifetime (L80/B20): 80000 h. (tq+25°C)
 Lifetime (L70/B20): 100000 h. (tq+25°C)
 Lifetime (L70/B10): 50000 h. (tq+45°C)
 Sudden decreased luminous flux after 50000 hours: 0% (C0).
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

SOURCE

4 linear LED modules 25W/840.
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.
 CCT nominal colour temperature 4000 K.
 Colour initial tolerance (MacAdam): SDCM 3.

MECHANICAL CHARACTERISTICS

Housing with double casing in pressed aluminium, powder-coated in white epoxy-polyester, hinged opening.
 Quick connection in polycarbonate M20x1.5 cable gland for access to the terminal block.
 Ecologic anti-aging injected sealing gasket.
 Stainless steel clips.
 Total flow recuperator in specular aluminium, with superficial titanium-magnesium treatment, non-iridescent.
 Transparent, non-combustible tempered glass.
 Fixing bracket for busbar or suspension in galvanised steel.
 Luminaire with limited surface temperature. - D -
 Dimensions: 680x680 mm, height 187 mm. Weight 10.975 kg.
 IP64 protection degree.
 Mechanical strength to impacts IK10 (20 joule).
 Glow-wire test resistance 960°C.

ELECTRICAL CHARACTERISTICS

Halogen Free electronic wiring 230V-50/60Hz, power factor >0.95, constant output current, class I, 2 driver.
 Twin-circuit.
 Power of the luminaire 110 W.
 ENEC - CE.
 Flicker: <4%.
 Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.
 Ambient temperature from -20°C to +45°C.
 Temperature class T6 max 85°C.
 Quick connection.
 Relative humidity UR: <85%.

INSTALLATION

Ceiling / Suspended.
 All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com.

APPLICATIONS

Areas with high ceilings, industrial/warehouses and open areas.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20210413 - Page 1 of 1

3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

Web www.3F-Filippi.com
e-Mail 3F-Filippi@3F-Filippi.it
Telephone +39.051.6529611
Fax +39.051.775884