


Scheda prodotto

| | | |
|---------------------------------------------------------------------|-------|----------------------------------------------------------------------------------------------------------------------------------|
| Manufacturer | |  2MXF40A2V1B CTXF20C5V1B CTXF25C5V1B |
| Outdoor unit | | |
| Indoor unit | | |
| Indoor unit | | |
| Outdoor sound power level (dB) | dB(A) | 60.0 |
| Indoor sound level | dB(A) | 55.0 |
| The refrigerant (GWP) | | R-32 (675) |
| Cooling mode | | |
| SEER | | 7.47 |
| Classe di efficienza energetica | | A++ |
| Annual electricity consumption | kWh/a | 188.0 |
| Design load Pdesignc | kW | 4.0 |
| Heating mode: Average climate Design temperature = -10°C | | |
| SCOP | | 4.26 |
| Classe di efficienza energetica | | A+ |
| Annual electricity consumption | kWh/a | 1052.0 |
| Design load Pdesignh at -10°C | kW | 3.2 |
| Required back up heating capacity at -10°C | kW | 0.73 |
| Declared capacity at -10°C | kW | 2.47 |
| Heating mode: Warm climate Design temperature = 2°C | | |
| SCOP | | |
| Classe di efficienza energetica | | |
| Annual electricity consumption | kWh/a | |
| Design load Pdesignh at 2°C | kW | |
| Required back up heating capacity at 2°C | kW | |
| Declared capacity at 2°C | kW | |
| Heating mode: Cold climate Design temperature = -22°C | | |
| SCOP | | |
| Classe di efficienza energetica | | |
| Annual electricity consumption | kWh/a | |
| Design load Pdesignh at -22°C | kW | |
| Required backup heating capacity at -22°C | kW | |
| Declared capacity at -22°C | kW | |

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2 Consumo di energia in base ai risultati della prova campione. Il consumo reale di energia è funzione della maniera in cui l'apparecchio viene utilizzato e della posizione in cui è collocato.